

HOT WATER IN 2 CLICKS... WHEREVER YOU WANT

DESIGNED AND MANUFACTURED IN ITALY

www.pleion-group.com







Hot Water in 2 clicks... wherever you want!

The world's most compact Solar Water Heater, the only one that can be installed on your own!



All the **PLEION EGO** family's innovations in a portable format.

In 130 cm *FreeGO* can generate up to 100 litres of hot water and is feither-weight at only 18 kg!

Just connect it to a tap and that's all, the sun will start heating the water and the water temperature is adjustable with an integrated thermostatic mixer (38°C - 60°C).







The perfect companion for your leisure time.

With the functionality and simplicity at the first place, *FreeGO* is always with you and provides you with hot water, may it be at home in the garden, on the top of a mountain or on the most remote beaches.

A unique design, the compactness and the easy way to be transported make it perfect for trips, but also for your everyday life and your hobbies, always and everywhere.

DO-IT-YOURSELF installation in just a few seconds!









1. Place it wherever you want

FreeGO is the world's most compact and lightest (only 18 kg) solar water heater that can be installed where you need it, on your own and in just a few seconds



2. Connect it to a tap Free Go is equipped with quick couplings that allow you

FreeGO is equipped with quick couplings that allow you to connect it in 2 clicks to the water supply you have available.




3. Adjust the temperature As soon as you have connected your *FreeGO* just adjust the desired

As soon as you have connected your *FreeGO* just adjust the desired outlet temperature and use the hot water that is produced by the sun.



4. Enjoy the Free Hot Water produced by the Sun!







IN BRASS







UNBREAKABLE FRONT COVER!

CELLULAR POLYCARBONATE LEXAN® THERMOCLEAR™:

UNBREAKABLE: 250 times more resistant than glass.

LIGHT-WEIGHT: 80% lighter than glass.

TRANSPARENCY: exceptional capacity to conduct the solar radiations and guaranteeing 10 years against yellowing (PATENTED).

PERFORMANCE: significant reduction of heat losses during

the night.


DOUBLE UV PROTECTION.

THERMOSTATIC REGULATION OF THE TEMPERATURE.

The integrated mixing system ensures the perfect comfort of the hot water's outlet temperature. With FREEGO you can obtain up to 9 minutes of continuously flowing hot water for 8 showers



TECHNICAL SPECIFICATIONS



FREEGO

COMPACT AND HIGH EFFICIENT DO-IT- YOURSELF SOLAR THERMAL SYSTEM FOR THE PRODUCTION OF DOMESTIC HOT WATER.

 Dimensions 	1255 x 635 x 216 mm

Total surface area of the collector
 Aperture area of the collector
 Absorption area
 Capacity
 Empty weight
 Weight when fully loaded
 Inclinations
 0,66 m²
 0,50 m²
 55 lt
 18 kg
 75 kg
 45°/40°/35°


• Water temperature at the outlet 38÷60°C Adjustable with Thermostatic

mixing valve with knob

• Maximum operating temperature **100°C**

• Operating pressure 3 bar

• Connections Quick coupling 1/2" GAS F







PLEION Srl Via Venezia, 11 - Cerea Verona infoline +39 0442 320295 info@pleion.it

Seguici su

